



Rec'd PET/PTO 07 MAR 2005  
10/527038  
INVESTOR IN PEOPLE

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QBP

REC'D 16 OCT 2003

PET

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 2 October 2003

**BEST AVAILABLE COPY**

Patent 1977



10025746702-1 002832  
000-0220858.5

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference	G093.001.00		
2. Patent application number (The Patent Office will fill in this part)	0220858.5		
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Nigel Francis <u>GAMBLE</u> Hanover Lodge 256 Seagrave Road Sileby Leicestershire LE12 7NJ		
Patents ADP number (if you know it)			
If the applicant is a corporate body, give the country/state of its incorporation	4381018002 <i>II</i>		
4. Title of the invention	Pusher apparatus for merchandise		
5. Name of your agent (if you have one)	SERJEANTS		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	25 The Crescent King Street Leicester LE1 6RX		
Patents ADP number (if you know it)	1461001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	No		

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

0

Description

8

Claim(s)

2

Abstract

1

Drawing(s)

4 x 4 SW

10. If you are also filing any of the following, state how many against each item.

Priority documents

0

Translations of priority documents

0

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

0

Request for preliminary examination and search (Patents Form 9/77)

1

Request for substantive examination (Patents Form 10/77)

1

Any other documents (please specify)

0

11. I/We request the grant of a patent on the basis of this application.

Signature

*[Signature]*

Date

Serjeants

06/09/2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Peter J. SMITH 0116 233 2626

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

TITLE

Pusher apparatus for merchandise

DESCRIPTION

5 Technical field

The invention relates to the field of pusher apparatus, i.e. apparatus for pushing a stack of items along a track. The main application for pusher apparatus is in merchandising of items for sale, whereby the front item of the stack of merchandise is always pushed to the front of the shelf. Pusher apparatus according to the invention  
10 may also operate vertically or at other angles and words such as "front", "forwards" and "backwards" in this specification are not intended to limit its scope to horizontal operation. Pusher apparatus may clearly also be used in other situations where items are to be dispensed to a user, not necessarily for sale.

15 Background

It is known to use a pusher apparatus for automatically pushing items of merchandise to the front of a shelf, where they are more readily visible and accessible to a potential purchaser. This may particularly promote one type of merchandise, which is stacked on a pusher apparatus and therefore prominent at the front of the shelf, over adjacent  
20 merchandise that remains at the back of the shelf.

A known pusher apparatus comprises a pusher unit that slides on a track. The pusher unit may be guided along the track by rails. The pusher unit is retracted against the force of a spring so that a stack of merchandise can be placed along the track. When  
25 the pusher unit is released, it urges the stack forwards until the front item of merchandise comes to rest against a lip at the front of the track. As each item of merchandise is removed, the remaining stack is urged forwards until the next item rests at the front of the track. Known springs in such pusher apparatus either have a concertina shape with one end attached to the back of the track and the other end  
30 attached to the pusher unit to push the pusher unit forwards; or have a coiled configuration with one end attached to the front of the track and the other end attached to the pusher unit to pull the pusher unit forwards.

~~The known pusher apparatus suffers various problems. One is that of "racking". If~~  
the merchandise being pushed is not centred on the pusher plate, there is a tendency  
for the pusher unit to cant to one side as it moves forwards. That can cause the pusher  
5 unit to wedge against the rails of the track, preventing further forward movement.  
The wider the pusher plate is, the greater is the potential turning moment of an off-  
centre load. This provides a practical limit to the width of the pusher plate and the  
size and weight of the merchandise that can be stacked on the apparatus.

10 In the prior art, the speed of the pusher has also been a problem. The spring must be  
strong enough to push a full stack of merchandise against the force of friction between  
the stack and the track. When the same spring is acting on only a few items in the  
stack, it can accelerate them violently and push them too rapidly along the track.  
There is a risk of injury to the fingers of a person who is loading the apparatus. There  
15 is also a risk that the rapidly moving items will be ejected from the front of the stack,  
causing them to fall and be damaged. To avoid the latter risk, the height of the  
retaining lip at the front of the track must be increased, which makes the items less  
visible and less accessible and requires a greater space above the shelf so that items  
can be lifted over the lip.

20 Known pushers have been found not to work well in cold environments such as chiller  
or freezer cabinets. There is a problem with the build up of frost along the track,  
which impedes the sliding movement of the pusher unit. There is also a problem of  
ice adhering the pusher unit to the track.

#### 25 Summary of the invention

The invention provides pusher apparatus comprising: a track; a pusher mounted on the  
track for movement along the track; a spring mounted on the pusher for urging the  
pusher along the track; an axle rotatably mounted on the pusher; and at least one  
30 wheel fixed to the axle for positively engaging the track.

Preferably, the track includes at least one line of slots or teeth along the track; and wherein each wheel is a cog bearing teeth for positively engaging the slots or teeth of the track.

- 5 In a highly preferred embodiment, at least two wheels are fixed to the axle for simultaneous rotation. Because the two wheels positively engage the track, the two ends of the axle can only move simultaneously and the two sides of the pusher unit must advance in step along the track. Therefore the pusher unit does not cant to either side and the problem of racking is solved. To prevent relative rotational movement of
- 10 the two wheels, the material of the axle must be sufficiently stiff under torsional stresses. For ordinary small and lightweight applications, plastics materials should suffice but for pushing heavy items with a wide pusher plate a stronger material such as steel may be required.
- 15 The spring may be a coil spring. In a preferred embodiment, the spring is coiled about the axle, one end of the spring being secured to the axle and the other end of the spring being attached to the pusher, whereby the coiling or uncoiling of the spring drives rotation of the axle. In this embodiment, the spring can be contained entirely within the housing of the pusher unit, where it is hidden from view and also protected
- 20 from dirt that may accumulate on the track. The pusher may be started from any point on the track then retracted and, as the spring unwinds, it will naturally return to its starting point.

25 In an alternative preferred embodiment, a first end of the coil spring is attached to a front end of the track and the second end of the spring is attached to the pusher, whereby the coiling of the spring draws the pusher along the track. In this embodiment the pusher is started from a fixed point at the end of the track and its forward movement ends when it returns to the fixed point. That is not necessarily when the spring is in a fully relaxed condition, which has the advantage that the

30 spring may still provide a useful driving force even near the end of the track. The same embodiment may further comprise a second axle rotatably mounted on the pusher, wherein the spring is coiled about the second axle and the second end of the

spring is attached to the second axle. By using separate axles for mounting the spring and the cogs, each axle can be designed optimally for its own function and it is not necessary to ensure that the number of turns on the spring matches the number of turns of the cogs.

5

As an alternative, the coil spring need not be mounted on an axle, provided that it is constrained to coil appropriately within a suitable housing.

10 The spring does not have to be located centrally on the track and if there is an independent spring axle, the independent axle need not be parallel to the gear axle. For example, the spring axle can have a vertical axis and the spring can run along a side wall of a channel in which the track is located.

15 The gear axle does not have to be perpendicular to the length of the track. With an oblique gear axle, each individual slot should extend parallel to the gear axle to accommodate a component of motion of the gear tooth parallel to the axle as the pusher slides along the track.

20 It is strongly preferred that the pusher apparatus comprises a rotary damper mounted on the pusher for regulating the rate of coiling or uncoiling of the spring. The damper allows the use of a spring strong enough to move the largest loads expected when the stack is full but prevents the pusher from moving too fast when only a light load is present. Therefore the problems of potential injury and of spilt merchandise are avoided. The damping effect of the rotary damper may be adjustable so that a single  
25 design of pusher apparatus can accommodate merchandise of widely differing weights. Other kinds of damper such as a linear damper arranged along the track could also be used.

30 The pusher apparatus preferably includes a latch for retaining the pusher at a desired position along the track, so that the operator can have both hands free when loading a stack of merchandise. The latch may be releasable by trigger means located at the

front end of the track. Alternatively, the latch may be releasable by applying rearward pressure to the pusher.

The drawings

5 Figure 1 shows a pusher apparatus according to a first embodiment of the invention in vertical cross section on line I-I of Figure 2.

Figure 2 shows the pusher apparatus of Figure 1 in plan view, sectioned along line II-II of Figure 1.

10 Figures 3 and 4 show the pusher apparatus of Figure 1 in a perspective view and illustrate the operation of the latch mechanism.

Figure 5 shows in perspective view a pusher apparatus according to a second embodiment of the invention.

15 Figures 6, 7 and 8 show the pusher apparatus of Figure 5 in plan view, side view and end view respectively, each view having part of the housing cut away to reveal the interior.

Detailed description of the preferred embodiments

The pusher apparatus shown in Figures 1 to 4 comprises an elongate track 2, which in use rests on or is integral with a shelf (not shown) for displaying merchandise. A  
20 pusher unit 4 is mounted on the track 2 so as to be capable of sliding along the track 2. Merchandise 6 for display is stacked along the track 2 and is engaged by a pusher plate 8 of the pusher unit 4.

A coil spring 10 is coiled about a spring axle 12 that is rotatably mounted in the  
25 pusher unit 4, one end of the spring being attached to a ring (not shown) freely rotatable on the spring axle 12. The other end of the spring is attached at 14 to the track 2, near to the front end of the track 2. As the pusher unit 4 is drawn back along the track to the position shown in Figure 1, the spring 10 uncoils and lies flat along the track 2. The natural tendency of the spring 10 to coil up again draws the pusher  
30 unit 4 forwards along the track 2, pushing the items of merchandise 6 on the track ahead of it, until the front item engages a lip 16 at the front end of the track 2. When the front item of merchandise is removed from the shelf, the spring 10 is free to re-

coil further and the pusher plate 8 pushes the remaining stack of merchandise 6  
forwards until the next item rests against the lip 16 at the front of the track 2.

5 A gear axle 20 is also mounted in the pusher unit 4 so as to be freely rotatable. Fixed  
to the gear axle 20 are two cogs 22, which therefore rotate simultaneously when the  
gear axle 20 rotates. When the pusher unit 4 rests on the track 2, the teeth of each cog  
22 engage a line of slots 24 in the track in a rack-and-pinion arrangement. As shown,  
the ends of the cog teeth are rounded to engage with rectangular slots 24. However  
any suitable shape of cog teeth may be used with complementary teeth or slots in the  
10 track, as is well known. Because the two cogs 22 are connected together by the rigid  
gear axle 20, the two sides of the pusher unit 4 must move forwards simultaneously  
and the pusher unit 4 is unable to cant to one side, which caused the racking problem  
in the prior art. Because of this resistance to racking, the pusher plate 8 in the  
apparatus of Figures 1 and 2 can be considerably enlarged and the apparatus can be  
15 used for bulky and heavy items of merchandise 6.

Rotation of the gear axle 20 is controlled by a rotary damper 18 mounted in the pusher  
unit 4. The rotary damper 18 is preferably a one-way damper so that the pusher unit 4  
may be easily retracted for filling the shelf but the forward movement of the pusher  
20 unit 4 under the influence of the spring 10 is controlled by the damper 18. The  
damping level of the rotary damper 18 should be selected so that when the shelf is full  
and the spring 10 is fully stretched, the merchandise 6 does not move forwards at too  
high a speed, which might cause it to tip over the lip 16 at the front of the track 2. On  
the other hand, the spring 10 must be able to overcome the resistance of the damper  
25 18 and the friction of the moving parts against the track 2 in order to move the final  
item of merchandise 6 when the spring 10 is almost fully coiled and at its weakest.  
The rotary damper 18 acts by a viscous fluid which resists the movement of vanes or  
valves (not shown) driven by rotation of the gear axle 20. If the pusher apparatus is to  
be used in a cold environment such as a freezer, the fluid becomes more viscous and  
30 the damping effect is increased.

The pusher apparatus is also provided with a latch, which holds the pusher unit 4 at the retracted position (shown in Figure 3) along the track 2, against the bias of the spring 10, to allow for ease of filling the shelf with merchandise 6. The latch 26 is connected by a rod 28 running beneath the track 2 to a trigger 30, by which the latch 26 may be released (as shown in Figure 4) to allow the pusher unit 4 to move along the track 2..

An alternative latch (not illustrated) may be a double-action latch fixed to the rear end of the track 2. When the pusher unit 4 is first pushed back against the latch, it latches and holds the pusher unit stationary against the bias from the spring 10. The pusher unit 4 may be pushed back a second time to release the latch. A still further alternative (not illustrated) may be to mount the latch entirely on the pusher unit 4. However, that is then more difficult to access when the pusher unit 4 is retracted and the shelf is full of merchandise.

Another embodiment of the invention, which is better suited to small and lightweight merchandise such as cigarette packets, is illustrated in Figures 5 to 8. A track 52 of  $\pi$ -shaped cross section may be mounted in a channel or between walls on a shelf (not shown) where merchandise is to be displayed. A pusher unit 54 is mounted so as to be slidable along the track 52. The pusher unit 54 has lugs 56 for engaging flanges 58 on the track 52 to prevent the pusher unit 54 from being lifted off the track 52.

Mounted for rotation in the pusher unit 54 is an axle 60. One end of the axle 60 engages a rotary damper 62 and the other end engages a bearing 64. Fixed to the axle 60 is a cog 66. When the pusher unit 54 is mounted on the track 52, the teeth of the cog 66 engage a line of slots 68 along the track 52 in a rack-and-pinion arrangement. As shown, the ends of the cog teeth are rounded to engage with rectangular slots 68. However any suitable shape of cog teeth may be used with complementary teeth or slots in the track, as is well known.

A coil spring 70 is coiled around the axle 60. One end of the coil spring is fixed to the axle 60 and the other end to a mounting 72 on the housing of the pusher unit 54.

Thereby, when the spring 70 coils or uncoils, the axle 60 rotates within the pusher unit 52 in the manner of a clockwork mechanism. The rate of rotation of the axle 60 is controlled by the rotary damper 62.

5 In use, the pusher unit 54 is mounted at the front end (not shown) of the track 52 with the coil spring 70 in its relaxed state. The pusher unit 54 is then pushed back along the track 52 causing the cog 66 to rotate the axle 60 and coil the spring 70 more tightly. A stack of merchandise items may then be placed on the track 52 in front of the pusher unit 54 and behind a front product stop (not shown). The product stop may  
10 be integral with, attached to or adjacent to the track 52. When the pusher unit 54 is released, the spring 70 attempts to uncoil and it urges the pusher unit 54 forwards along the track 52 until the front item of merchandise rests against the product stop at the front of the track 52. As each item of merchandise is removed, the spring 70 uncoils further and the pusher unit 54 moves the stack of merchandise forwards so  
15 that an item is always presented at the front of the shelf. When the last item is removed and the pusher unit 54 reaches the front of the track 52 once more, the coil spring 70 is then back in its relaxed state and the forward movement ceases.

This embodiment of the invention is capable of working with tracks that bend  
20 upwards or downwards or (within certain limits of curvature) sideways, which may allow the design of attractive and unusual merchandising displays.

One or more hybrids between the two illustrated embodiments of the invention are also possible. For example, the spring 70 contained wholly within the pusher unit 54  
25 of the second embodiment may be combined with the twin cogs 22 and track 2 of the first embodiment to resist racking. In that case, the cogs 22 and the spring 70 will share a common axle.

CLAIMS

1. Pusher apparatus comprising:  
a track;  
5 a pusher mounted on the track for movement along the track;  
a spring mounted on the pusher for urging the pusher along the track;  
an axle rotatably mounted on the pusher; and  
at least one wheel fixed to the axle for positively engaging the track.
- 10 2. Pusher apparatus according to claim 1, wherein the track includes at least one line of slots or teeth along the track; and wherein each wheel is a cog bearing teeth for positively engaging the slots or teeth of the track.
- 15 3. Pusher apparatus according to claim 1 or claim 2, comprising at least two wheels fixed to the axle for simultaneous rotation, wherein each wheel positively engages the track.
- 20 4. Pusher apparatus according to any of claims 1 to 3, wherein the spring is a coil spring.
- 25 5. Pusher apparatus according to claim 4, wherein the spring is coiled about the axle, one end of the spring being attached to the axle and the other end of the spring being attached to the pusher, whereby the coiling or uncoiling of the spring drives rotation of the axle.
- 30 6. Pusher apparatus according to claim 4, wherein a first end of the spring is attached to a front end of the track and the second end of the spring is attached to the pusher, whereby the coiling of the spring draws the pusher along the track.
7. Pusher apparatus according to claim 6, further comprising a second axle mounted on the pusher, wherein the second end of the spring is coiled about the second axle.

8. Pusher apparatus according to any of claims 4 to 7, further comprising a rotary damper mounted on the pusher for regulating the rate of coiling or uncoiling of the spring.

5

9. Pusher apparatus according to claim 8, wherein the damping effect of the rotary damper is adjustable.

10. Pusher apparatus according to any preceding claim, further comprising a latch  
10 for retaining the pusher at a desired position along the track.

11. Pusher apparatus according to claim 10, wherein the latch is mounted on the track and is releasable by trigger means located at the front end of the track.

15 12. Pusher apparatus according to claim 10, wherein the latch is mounted on the track and is releasable by applying rearward pressure to the pusher.


TITLE


Pusher apparatus for merchandise


ABSTRACT





A pusher apparatus comprises a track (2,52), a pusher (4,54) mounted on the track (2,52) for movement along the track; a spring (10,70) mounted on the pusher (4,54) for urging the pusher along the track (2,52); an axle (20,60) rotatably mounted on the pusher (4,54); and at least one wheel (22,66) fixed to the axle (20,62) for positively engaging the track (2,52). In one aspect of the invention, two of the said wheels (22) are fixed to the axle (20) to avoid canting of the pusher (4) as it moves along the track (2). In another aspect of the invention, the spring (70) is a coil spring contained within the pusher unit (54) for driving rotation of the axle (60). Preferably, a rotary damper (18,62) regulates the operation of the coil spring (10,70).

(Fig. 1)









**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**